

SPECIFICATIONS

EQUIPMENT

5 HP, 1685 RPM, 550 V, GENERAL ELECTRIC, 254X, SLIP RING CRANE MOTOR

HORSEPOWER	5
SPEED	1685
STATOR VOLTAGE 1	550
STATOR VOLTAGE 2	
MANUFACTURER	GENERALELECTRIC
TYPE	MR
FRAME	254X
SHAFT HEIGHT	6 1/4
ROTOR AMPS	19
ROTOR VOLTAGE	140
SHAFT EXTENSION	DESS
ENCLOSURE	DPBB
STATOR AMPS	5.55
BEARINGS	A/F
MODEL OR STYLE	5MR4254A21Y4-A
SERIAL OR ID	
PHASE	3
DUTY	30
DEGREE OF TEMP RISE	
WEIGHT	
AGE	
DRIVE SHAFT DIAMETER	1 3/8
DRIVE SHAFT LENGTH	4
BRAKE SHAFT DIAMETER	1 3/8 TO 1 1/8
BRAKE SHAFT LENGTH	4 3/4
OVERALL LENGTH	
FRONT BOLT HOLE TO SHAFT	
WIDTH BETWEEN FEET	
LENGTH BETWEEN FEET	

INVENTORY ID: 101509-000-00

Page 1 of 1

CASEY

275 Kappa Drive, Pittsburgh, PA 15238

Ph: (800) 882-7000 • (412) 963-1111

Fax: (412) 963-0808 • E-mail: info@caseyusa.com

Web: www.caseyusa.com