

# SPECIFICATIONS

## 20 TON BLISS NON-MOTORIZED COIL CAR

EQUIPMENT

MANUFACTURER: E. W. BLISS  
AGE: 1964

**GENERAL SPECIFICATION:**

CAPACITY: 20 TONS

COIL: 24" WIDE MIN. (61 MM)  
50" WIDE MAX. (1270 MM)  
72" O.D. MAX. (1829 MM)  
30" O.D. MIN. (762 MM)

COIL LIFT HEIGHT: 49" (1245 MM)

NO. OF WHEELS: 4

WHEEL SIZE: 15" DIA. (381 MM)

WHEEL CENTERLINE: 59" (1499 MM)

TRACK GAUGE: 40-1/2" (1029 MM)

HYDRAULIC TRAVERSE

CYLINDER: 8" DIA. (203 MM)  
202" STROKE (5131 MM)

HYDRAULIC LIFT CYLINDER: 12" DIA. (305 MM)  
49-1/2" STROKE (1257 MM)

FACE PLATE WITH ROLLS: (2) 9" DIA. X 24" FACE (229 X 610 MM)

DIMENSIONS: 96-1/4" DEEP X 45" WIDE X 75" LENGTH  
(2445 X 1143 X 1905 MM)

PREVIOUS USE: TEMPER MILL TENSION REEL

104313-000-00 (GP0160)

# CASEY

275 Kappa Drive, Pittsburgh, PA 15238  
Ph: (800) 882-7000 • (412) 963-1111  
Fax: (412) 963-0378 • E-mail: [info@caseyusa.com](mailto:info@caseyusa.com)  
Web: [www.caseyusa.com](http://www.caseyusa.com)