

SPECIFICATIONS

30,000 CFM S. P. KINNEY BURNER

EQUIPMENT

MANUFACTURER: S. P. KINNEY
AGE: 1989
SERIAL NO.: 192
QUANTITY: TWO (2) ONE COMPLETE
ONE SHELL

GENERAL SPECIFICATION:

CAPACITY: 30,000 CFM

TYPE: MOTOR OPERATED

APPLICATION: AIR / GAS

VALVE TRAVEL: 18" NORMAL
6" ADDITIONAL TO REMOVE VALVE
24" TOTAL

AIR CONNECTION 30" O.D. PIPE AT 30° OFF VERTICAL
FLANGE: 38-3/4" O.D
36" BOLT CIRCLE
28-13/16" DIA. HOLES EQUALLY SPACED TO STRADDLE CENTERLINES

GAS CONNECTION 30" O.D. PIPE
FLANGE: 38-3/4" O.D
36" BOLT CIRCLE
28-13/16" DIA. HOLES EQUALLY SPACED TO STRADDLE CENTERLINES

GAS VENT: 6" DIA.

GAS CHAMBER: 42" I.D.

PREVIOUS USE: BLAST FURNACE STOVES

FEATURES: · PEEP SIGHT
· GAS CHAMBER CLEANOUTS
· EXPLOSION DOOR
· DUST COLLECTION CHAMBER WITH FLUSHING CONNECTIONS

104323-000-00 (GP0175)

CASEY

275 Kappa Drive, Pittsburgh, PA 15238

Ph: (800) 882-7000 • (412) 963-1111

Fax: (412) 963-0378 • E-mail: info@caseyusa.com

Web: www.caseyusa.com