

SPECIFICATIONS

EQUIPMENT

25HP, 690 RPM, 440 V, GENERAL ELECTRIC, 404Z, SLIP RING CRANE MOTOR

HORSEPOWER	25
SPEED	690
STATOR VOLTAGE 1	440
STATOR VOLTAGE 2	
MANUFACTURER	GENERALELECTRIC
TYPE	MR
FRAME	404Z
SHAFT HEIGHT	10
ROTOR AMPS	50
ROTOR VOLTAGE	234
SHAFT EXTENSION	DESS
ENCLOSURE	TENV
STATOR AMPS	45
BEARINGS	A/F
MODEL OR STYLE	
SERIAL OR ID	
PHASE	3
DUTY	60
DEGREE OF TEMP RISE	
WEIGHT	
AGE	
DRIVE SHAFT DIAMETER	2 7/8
DRIVE SHAFT LENGTH	6
BRAKE SHAFT DIAMETER	2 1/2
BRAKE SHAFT LENGTH	4
OVERALL LENGTH	
FRONT BOLT HOLE TO SHAFT	
WIDTH BETWEEN FEET	
LENGTH BETWEEN FEET	

CASEY

275 Kappa Drive, Pittsburgh, PA 15238

Ph: (800) 882-7000 • (412) 963-1111

Fax: (412) 963-0808 • E-mail: info@caseyusa.com

Web: www.caseyusa.com