

SPECIFICATIONS

EQUIPMENT

400HP, 1150/1500RPM, 500V, GENERAL ELECTRIC, STAB SHUNT, DC MOTOR

| | |
|----------------------|-----------------|
| HORSEPOWER | 400 |
| SPEED | 1150 |
| SPEED 2 | 1500 |
| VOLTAGE | 500 |
| MANUFACTURER | GENERALELECTRIC |
| FRAME | CD685AS |
| TYPE | AS |
| WINDING | SHUNT |
| ENCLOSURE | SPFG |
| SHAFT | SESS |
| AMPERAGE | 645 |
| DUTY | CONTINUOUS |
| BEARINGS | A/F |
| AGE | |
| DEGREE OF TEMP RISE | 40 |
| FIELD VOLTAGE | |
| FIELD AMPERAGE | 7.6/4.8 |
| FIELD RESISTANCE | 25 DEG C 29.5 |
| SERIAL OR ID # | FV240 |
| MODEL OR STYLE # | 5CD24E |
| SERVICE FACTOR | 28F900025 |
| INSULATION CLASS | F |
| CODE | C |
| WEIGHT | 4500 |
| DRIVE SHAFT DIAMETER | 2 1/8" |
| DRIVE SHAFT LENGTH | 6 3/4" |
| BRAKE SHAFT DIAMETER | |
| BRAKE SHAFT LENGTH | |
| SHAFT HEIGHT | |
| SHAFT LENGTH | |
| WIDTH BETWEEN FEET | |
| LENGTH BETWEEN FEET | |

INVENTORY ID: 102424-000-00

CASEY

275 Kappa Drive, Pittsburgh, PA 15238

Ph: (800) 882-7000 • (412) 963-1111

Fax: (412) 963-0808 • E-mail: info@caseyusa.com

Web: www.caseyusa.com