

SPECIFICATIONS

EQUIPMENT

250 HP, 710 RPM, P&H, 440V, HEW686X AC SLIP RING CRANE MOTOR (R)

HORSEPOWER	250
SPEED	710
STATOR VOLTAGE 1	440
STATOR VOLTAGE 2	
MANUFACTURER	P&H
TYPE	HEW
FRAME	686X
SHAFT HEIGHT	
ROTOR AMPS	267
ROTOR VOLTAGE	437
SHAFT EXTENSION	DETS
ENCLOSURE	TEFC
STATOR AMPS	307
BEARINGS	A/F
MODEL OR STYLE	
SERIAL OR ID	500886 A
PHASE	3
DUTY	CONTINUOUS
DEGREE OF TEMP RISE	
WEIGHT	4,200
AGE	
DRIVE SHAFT DIAMETER	
DRIVE SHAFT LENGTH	
BRAKE SHAFT DIAMETER	
BRAKE SHAFT LENGTH	
OVERALL LENGTH	
FRONT BOLT HOLE TO SHAFT	
WIDTH BETWEEN FEET	
LENGTH BETWEEN FEET	

CASEY

275 Kappa Drive, Pittsburgh, PA 15238
Ph: (800) 882-7000 • (412) 963-1111
Fax: (412) 963-0808 • E-mail: info@caseyusa.com
Web: www.caseyusa.com