

**300 HP, 880 RPM, 440 V, GENERAL ELECTRIC, 6353AS, AC SLIP RING MOTOR,
WOUND ROTOR INDUCTION MOTOR**

HORSEPOWER	300
SPEED	880
STATOR VOLTAGE 1	440
STATOR VOLTAGE 2	
TYPE	M
MANUFACTURER	GENERALELECTRIC
FRAME	6353AS
ROTOR AMPS	282
ROTOR VOLT	496
SHAFT EXTENSION	SESS
ENCLOSURE	TEFC
AMPERAGE	349
BEARINGS	A/F
MODEL OR STYLE NUMBER	5M26353A
SERIAL OR ID NUMBER	8225406
PHASE	3
DUTY (MINUTES)	CONTINUOUS
DEGREE OF TEMP RISE	
WEIGHT	8,800
AGE	
DRIVE SHAFT DIAMETER	4 3/8
DRIVE SHAFT LENGTH:	8 1/4
BRAKE SHAFT DIAMETER:	
BRAKE SHAFT LENGTH:	
SHAFT HEIGHT	
OVERALL LENGTH	100"
FRONT BOLT HOLE TO SHAFT	
WIDTH BETWEEN FEET	41 1/2"
LENGTH BETWEEN FEET	26 7/8"

INVENTORY ID: 106377-000-00

