

# 54" (1372 MM) WIDE BLAWNOX EXIT TENSION REEL

MANUFACTURER: BLAWNOX  
AGE: 1963  
SERIAL NO.: 50906

## GENERAL SPECIFICATIONS

CAPACITY: 24" TO 48" WIDE COIL (610 MM TO 1219 MM)  
.047" TO .220" GAUGE (1.19 MM TO 6 MM)  
84" O.D. (2134 MM)  
20" & 24" I.D. (508 MM & 610 MM)  
60,000 LBS.  
1200 PIW

TYPE: 3 PIECE EXPANDABLE MANDREL

MANDREL: 20" DIA. X 56" FACE (508 MM X 1422 MM)  
19" & 23" COLLAPSED (483 MM & 584 MM)  
20" & 24" EXPANDED (508 MM & 610 MM)

GEARBOX: 36:1 RATIO

DRIVE: 100 HP WEST MOTOR  
684A FRAME  
400 - 1600 RPM  
240V VOLTS DC

TRAVEL: RIGHT-HAND

MOVEMENT: 11" ON CARRIAGE SLIDE (279 MM)

COIL PUSHOFF: 56" STROKE (1422 MM)

REEL HEIGHT: 64" TO CENTERLINE (1626 MM)

SPEED: 250 FPM

PREVIOUS USE: COIL PREP LINE

DIMENSIONS: 26' LENGTH X 9' WIDTH X 8' HEIGHT  
(8 M LENGTH X 3 M WIDTH X 2 M HEIGHT)

INVENTORY ID: 107341-000-00 (YM 3576)

**CASEYUSA®**

Revised 8/22/2011

**CASEY**

275 Kappa Drive, Pittsburgh, PA 15238

Ph: (800) 882-7000 • (412) 963-1111

Fax: (412) 963-0378

E-mail: [mechanicalsales@caseyusa.com](mailto:mechanicalsales@caseyusa.com)

Web: [www.caseyusa.com](http://www.caseyusa.com)