

4" (102 MM) HUNT DESCALE VALVES

MANUFACTURER: HUNT VALVE COMPANY
AGE: PRIOR TO 1991
MODEL: R80156/V800-440-02
SIZE: 4" VALVE BODY

GENERAL SPECIFICATION:

RATING: 3000 PSI, 339 GPM AT 25 FEET PER SECOND
FLOW RATE WITH 3" SCHEDULE 160 PIPE
1900 PSI, 414 GPM AT 25 FEET PER SECOND FLOW
RATE WITH 3" SCHEDULE 80 PIPE

TYPE: TWO WAY, TWO POSITION VALVE MEGA FLOW A

PREVIOUS USE: HOT STRIP DESCALING SYSTEM

FEATURES: PNEUMATICALLY OPERATED
3" FLANGES INLET/DISCHARGE 1500 LBS.
NORMALLY CLOSED, NO PILOT VALVE, BODY CASTING V038-804
INLET/OUTLET FLANGES OPPOSED 180°
TWO AVAILABLE WITH SETUP STANDS

NOTE: 4" HOUSING 500 UP TO 785 GPM BUT 3" FLANGES LIMIT FLOW RATE

REBUILT 10-1/2" FLANGE: R85896 TAG NO.
REBUILT 6" FLANGE: 487933 (8/9/91) TAG NO.

10-1/2" FLANGE & 8 BOLT HOLES: 107415-000-00; 107416-000-00; 107417-000-00; 107418-000-00;
6" FLANGE: 107422-000-00; 107423-000-00
ALL AVAILABLE SEPARATELY

CASEYUSA®

CASEY

275 Kappa Drive, Pittsburgh, PA 15238

Ph: (800) 882-7000 • (412) 963-1111

Fax: (412) 963-0378 • E-mail: info@caseyusa.com

Web: www.caseyusa.com