

(6) 600 AMP 2,400 VOLT S&C 3-POLE MINI INTERRUPTOR SWITCHES

- S & C Custom Switchgear
- 11 vertical indoor dust proof enclosures consisting of:
- (6) 600 amp 2,400 3-pole Mini Interrupter Switches with 11 gauge reinforced sheet steel
- Aluminum buss
- UL listed, category B – ANST/TEEE , C37 .20.3
- Manufactured in 1993

- Previously used with a 2500 KVA 2400 volt transformer
- Has:
 - 2- Cable Entry in bays 1 and 6
 - 2- SM% parallel fused bays 2 and 7
 - 2- Buss Transition bays 3 and 9
 - 1-Tie Switch bay 8
 - 4 – Distribution Switches bays 4,5,10 and 11

All doors have provisions for pad locking. Doors cannot be opened if the Switch is closed. Switches can not be closed if the Doors are open

Condition: Excellent

VERTICAL SECTION #1 - CABLE ENTRY

- (3) CT'S GE 600/5
- (2) PT'S 750/500 KVA 30 DEGREE C/55 DEGREE C, 2400 V
20:1 CAT# 763421G25
- (3) FUSES 4.8KV 1/2 E AMP CAT 27000
- POWER LOGIC CIRCUIT MONITOR
- METER 0-10 AMPS
- EXTERNAL TEST STRIP
- 250,000 SHORT CIRCUIT RATING
- ENCLOSURE CAT B
- 600 AMP BUSS

VERTICAL SECTION #2

- S&C 14.4-17KV DISCONNECT SWITCH CAT# 255222R1-G3W
600 AMP CONTINUOUS, MOMENTARY RMS 40.000
- (6) 300E FUSES (2 PER PHASE), TYPE 5S, CAT#86641R2,
7.2 - 8.3 KV, REFILL UNIT SM-5
- KEY LOCK

VERTICAL SECTION #3 - BUSS TRANSITION

- VERTICAL BUSS - 120" W X 36" 48" D

VERTICAL SECTION #4

- S&C 14.4 - 17 KV DISCONNECT SWITCH CAT# 255222R1-G3, 600 AMP
CONTINUOUS, MOMENTARY RMS 40.000
- (3) 250E FUSES, TYPE 5S, CAT#86641RS, 7.25 8.3 KV, REFILL UNIT SM-5
0 -10 AMP METER ON DOOR
- KEY LOCK

VERTICAL SECTION #5

- S&C 14.4 - 17 KV DISCONNECT SWITCH CAT# 255222R1-G3, 600 AMP
CONTINUOUS, MOMENTARY RMS 40.000
- (3) 250E FUSES, TYPE 5S, CAT#866414S, 7.25 8.3 KV, REFILL UNIT SM-5
0 -10 AMP METER ON DOOR
- KEY LOCK

VERTICAL SECTION #6 - CABLE ENTRY

- (3) CT'S, GE 600/5
- (2) PT'S GE 750/500 KVA, 30 DEG. C 2400V 20:1 CAT# 763421G25
- (3) FUSES 4.8 KV, 1/2 E AMP CAT#27000
- POWER LOGISTICS MONITOR:
- METER 0-10 AMPS
- EXTERNAL TEST STRIP
- 250,000 SHORT CIRCUIT RATING
- ENCLSOURE CAT B
- 600 AMP BUSS

VERTICAL SECTION #7

- S&C 14.4 - 17KV DISCONNECT SWITCH CAT# 255222R1-G3W
600 AMP CONTINUOUS, MOMENTARY RMS 40.000
- (6) 300 E FUSES (2 PER PHASE), TYPE 5S, CAT#86641R2, 7.2 - 8.3 KV
REFILL UNIT SM-5
- KEY LOCK

VERTICAL SECTION #8

- 600 AMP DISCONNECT SWITCH
- 14.4 - 17 KV CAT #255222R1-G3W
- BOTTOM FEED

VERTICAL SECTION #9

- VERTICAL BUS WITH 0 - 10 AMP METER FOR BAYS 9.10 & 11

VERTICAL SECTION #10

- S&C 14.4 - 17KV DISCONNECT SWITCH CAT# 255222R1-G3
600 AMP CONTINUOUS, MOMENTARY RMS 40.000
- (3) 250 E FUSES, TYPE 5S, CAT#86641R2, 7.2 - 8.3 KV, REFILL UNIT SM-5
- KEY LOCK

VERTICAL SECTION #11

- S&C 14.4 - 17KV DISCONNECT SWITCH CAT# 255222R1-G3
600 AMP CONTINUOUS, MOMENTARY RMS 40.000
- (3) 250 E FUSES, TYPE 5S, CAT#86641R2, 7.2 - 8.3 KV, REFILL UNIT SM-5
- KEY LOCK

HORIZONTAL SECTION - CROSS OVER DUCT

INVENTORY ID: 115266-000-01

PAGE 1 OF 1